

Multifoils Direct

Experts in Foil Insulation Solutions

- Leading SuperQuilt Distributor
- Next Working Day Delivery
- Bulk Discounts Available
- Lowest Online Trade Rates

U-value calculation by BRE U-value Calculator version 2.04a - Printed on 25 Mar 2024 at 13:34

Filename: TrioQuilt 0.15 U-value - 175mm+ Rafters, 600mm Centres.uva (File saved: 25 Mar 2024 13:34)

Element type: Roof - Pitched roof - insulated slope, sloping ceiling - Calculation Method: BS EN ISO 6946

TrioQuilt 0.15 U-value - 175mm+ Rafters, 600mm Centres

<u>Layer</u>	<u>d (mm)</u>	<u>λ_{layer}</u>	<u>λ_{bridge}</u>	<u>Fraction</u>	<u>R layer</u>	<u>R bridge</u>	<u>Description</u>
1	12.5	0.210			0.100		Rsi
2	25	R-value ¹	0.130	0.0630	0.490	0.192	Plasterboard (standard wallboard)
3	7	R-value	R-value	0.0120	1.520	0.670	25mm Battens
4	25	R-value ²	0.130	0.0630	0.040	0.192	SuperQuilt
5	7	R-value	R-value	0.0120	1.520	0.670	25mm Batten
6	25	R-value ³	0.130	0.0833	0.490	0.192	SuperQuilt (Under Rafters - Taut)
7	100	0.040	0.130	0.0833	2.500	0.769	25mm Rafters / Cavity
8	50	R-value	0.130	0.0833	0.160	0.385	100mm Rafters / EcoLoft Non-Itch
9							50mm Rafters / Cavity
10	25	R-value					Breather membrane
11	15	1.000					25mm Battens
<hr/>				<u>0.100 #</u>			Tiles (clay)
<hr/>				<u>292 mm</u> (total roof thickness)	<u>6.980</u>		Rse

¹Calculated with specified emissivity of 0.02

²Calculated with specified emissivity of 0.02

³Calculated with specified emissivity of 0.02

this resistance substitutes for Rse and the resistance of layers 10-11 because of the ventilated air layer (layer 10)

Total resistance: Upper limit: 6.749 Lower limit: 6.450 Ratio: 1.046 Average: 6.599 m²K/W

U-value (uncorrected) 0.152

U-value corrections

Air gaps in layer 7 $\Delta U = 0.000$ (Level 0)

No fixings in layer 5

Total ΔU 0.000

U-value (corrected) 0.152

U-value (rounded) **0.15 W/m²K**

Calculated By:

Multifoilsdirect.co.uk, Callywhite Lane, Derbyshire, S18 2XP
0333 577 0288, Sales@multifoilsdirect.co.uk, www.multifoilsdirect.co.uk